

# CE-2517

CE-2517 is an insulating, self-amalgamating tape based on EPR (Ethylene Propylene Rubber).

## DESCRIPTION

Supplied in an easy to handle and apply tape form. The product is interleaved with a disposable plastic liner.

Its color is black.

Care should be taken to avoid direct contact between the tape and petroleum-type solvents and oils. Oils may affect the electrical properties of the tape.

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C.

Under these conditions, the storage life of the tape in a temperate climate will be at least 5 years.



**CORE :** 38 MM DENSE PLASTIC

**ROLL WIDTH :** 19 MM, 25 MM, 38 MM, 50 MM

**ROLL LENGTH :** 3 M, 5 M, 9,1 M, 10 M

**PACKAGING :** INDIVIDUALLY SHRINK-WRAPPED ROLLS

**SERVICE TEMPERATURE :** -40°C À +100°C

## SPECIFICATIONS

- For jointing and repairing a wide range of solid dielectric power cables up to 69 kV.
- For insulation, waterproofing and protection of electrical components.
- Excellent physical and electrical properties with a high degree of stability under conditions of use.
- The tape amalgamates rapidly when applied under tension to provide a void-free homogeneous wrapping.
- Compatible with a wide range of rubber and plastic dielectric cable insulation. These include polyethylene.
- Excellent resistance to water and ozone.
- The tape will remove cleanly when cut, allowing it to be used as temporary insulation or protection.

Reference	Code	Dimensions (m x mm)	Technical Properties	Nominal Value	Unit	Test Method
CE-2517	020 000	9,10 x 19	Dielectric strength	42	kV/mm	ASTM D149
CE-2517	020 001	4,5 x 25	Dielectric loss angle	0,005	-	ASTM D150
			Thickness	0,75	mm	-
			Volume resistivity	1 x 10 <sup>13</sup>	Ohm.m	ASTM D257
			Elongation at break	900	%	BS 903
			Tensile strength	3	Mpa	BS 903