

CE-2702

CE-2702 is a 'Premium' quality self-extinguishing electrical PVC adhesive tape.

DESCRIPTION

CE-2702 is a 0.13mm premium quality, electrical self-extinguishing soft PVC tape that uses an aggressive pressure sensitive rubber-based adhesive system. It has been designed for use where a recognized specification or international standard is required and where environmental safety is a concern.

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +5°C and +25°C. Use within 24 months from the date of manufacturing.

The tape should be applied with sufficient tension to ensure an optimum bonding and a minimum of two layers with a half overlap.

The final layer should be wrapped with a lower tension to prevent flagging effects. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.



CORE : 32 MM CARDBOARD CORE

ROLL WIDTH : 12, 15, 19 ET 25 MM

ROLL LENGTH : 10, 20, 25 ET 33 M

PACKAGING : CELLOPHANE WRAPPED WITH LABEL AND BAR CODE

COLORS : BLACK, WHITE, GREY, RED, BLUE, YELLOW, DARK GREEN, LIGHT GREEN, BROWN, ORANGE, VIOLET, TRANSPARENT, YELLOW/GREEN

SPECIFICATIONS

- Hand application
- Primary electrical insulation
- Harnessing
- Protection for low and medium voltage cable splices
- Colour coding
- Good resistance to abrasion, corrosion and moisture
- High dielectric strength and good mechanical protection
- Outstanding conformability
- Tape can be applied at low temperature (till -10°C)
- IMQ and VDE Approval Certificates according to IEC 60454-3-1
- Conforms to the European Directive 2011/65/EC (RoHS 2) and Commission Delegated Directive (EU) 2015/863 (RoHS 3)
- Index temperature 0°C to 90°C
- UL 510A - Recognized Tape OANZ2 : File E509583

Reference	Code	Dimensions (m x mm)	Technical Properties	Nominal Value	Unit	Test Method
CE-2702 - BLACK	020 050	10 x 19	Dielectric strength	40	kV/mm	IEC 60454-2
CE-2702 - BLACK	020 051	10 x 15	Tensile strength	25	N/cm	IEC 60454-2
CE-2702 - BLACK	020 052	25 x 19	Thickness	0	mm	IEC 60454-2
CE-2702 - TRANSPARENT	020 053	10 x 50	Volume resistivity	Flame-retardant	-	IEC 60454-2
CE-2702 - BLACK	020 054	10 x 50	Elongation at break	180	%	IEC 60454-2
CE-2702 - TRANSPARENT	020 055	25 x 50	Adhesion on steel	1,8	N/cm	IEC 60454-2
CE-2702 - RED	020 056	10 x 19	Adhesion on the backing	1,8	N/cm	IEC 60454-2
CE-2702 - RED	020 057	20 x 19				
CE-2702 - BLACK	020 058	20 x 19				
CE-2702 - WHITE	020 059	25 x 19				